

SINCE 1882, LEADING THE WAY WITH YOU



Product Catalogue



THE IDEAL FLUID RANGE FOR ALL YOUR NEEDS.



A LONG AND SUCCESSFUL HISTORY



1882

Oleoblitz has meant lubricants since 1882. The long and glorious history of motorization is enclosed in its name and Italian origins.



1910

Founded in **Milan**, Oleoblitz produced **lubricants for industrial** use until 1910, the year of creation of the automotive department. This turning point is linked to the association of the brand with the legendary **Isotta Fraschini** and to **some motoring legends** of **Tazio Nuvolari** and **Giuseppe Campari's** caliber.



1970

The sale to the Fuchs oil company in 1970 coincides with the economic boom relating to the automotive market. It is in this period that Oleoblitz proves to be a cutting-edge reality in the **formulation of products**, in the production of packaging and, again, in the formation of a widespread and structured agent network.



1987

In 1987 Oleoblitz was purchased by the **FL Selenia** group, leaving the industrial products sector to Fuchs.



2007

Starting from the end of 2007, it has been part of the **Petronas Lubricants Italy group** after the FL Selenia group is sold to Petronas.




2021

The new generation.

ALL THE ITALIAN LUBRICANTS EXPERIENCE

Oleoblitz is the complete range of specific products for **cars, industrial vehicles, agricultural vehicles** of all brands and models.

From engine to transmissions, from brakes to antifreeze and protection, the technology developed by Oleoblitz in over a century of history considers the different functions of the vehicle and respects the highest quality standards. Competence, research and assistance at a global level are the strengths of a brand capable of inventing and reinventing itself, managing to establish its brand as one of the most well-known lubricants realities.





PULSAR FE C3



COD. 70643

Specifications:
SAE 0W-30; API SN;
ACEA C3.

Performance level:
MB 229.51, 229.52;
Renault RN 0700.

PRODUCT DESCRIPTION

Oleoblitz Pulsar FE C3 0W-30 is a synthetic technology lubricant, designed for passenger cars using direct injection turbocharged gasoline engines and diesel engines where manufacturer recommends API SN, ACEA C3 specifications (please refer to the owner's manual).

It is also suitable for SUVs and vehicles running on biofuels and equipped with after treatment exhaust system and emission control devices such as DPF and catalytic converters; fuel injectors, multi-valves, turbochargers.



PULSAR FE C2

COD. 70642

Specifications: SAE 0W-30; ACEA C2.
Performance level: PSA B71 2312.



PULSAR F C4

COD. 70585

Specifications: SAE 5W-30; ACEA C4.
Performance level: MB 229.51, 226.51;
Renault RN0720; FCA 955535-S4.



PULSAR F C3

COD. 70658

Specifications: SAE 5W-30; API SN;
ACEA C2,C3.
Performance level: MB 229.51, 229.52;
VW 505.00, 505.01; BMW LL-04; GM Dexos 2.



PULSAR F PROGRESS

COD. 70659

Specifications: SAE 5W-30; API SP/CF;
ACEA C3.
Performance level: MB 229.51; VW 504.00,
507.00; BMW LL-04.



PULSAR F C2

COD. 70657

Specifications:
SAE 5W-30; ACEA C2.
Performance level: PSA B71 2290;
FCA 955535-S1.



PULSAR F PERFORMANCE

COD. 70388

Specifications:
SAE 5W-30; API SL/CF; ACEA A5/B5.
Performance level: Ford WSS-M2C913-C,
WSS-M2C913-D; Renault RN0700;
FCA 955535-G1.



PULSAR S TECHNO

COD. 70384

Specifications: SAE 5W-40; API SN/CF; ACEA C3;
Performance level: MB 229.51; VW 505.00,
505.01; BMW LL-04; GM Dexos 2;
Ford WSS-M2C917-A; Renault RN0700,
RN0710; FCA 955535-S2.



PULSAR S 5W-40

COD. 70383

Specifications: SAE 5W-40; API SN/CF; ACEA A3/B4.
Performance level: MB 229.5; VW 502.00,
505.00; BMW LL-01; GM-LL-B-025;
Renault RN0700, RN0710; FCA 955535-H2,
955535-N2, 955535-M2.



PULSAR S TURBO

COD. 70584

Specifications: SAE 10W-40; API SN/CF;
ACEA A3/B4.
Performance level: MB 229.1; VW 501.01,
505.00; Renault RN0700; PSA B71 2300;
FCA 955535-G2/955535-D2.



PULSAR M 15W-40

COD. 70581

Specifications: SAE 15W-40; API SL/CF;
ACEA A3/B3.
Performance level: MB 229.1;
VW 501.00, 505.00.



PULSAR M 20W-50

COD. 70583

Specifications: SAE 20W-50; API SJ;
ACEA A3/B3.
Performance level: MB 229.1; VW 501.00,
505.00.



HERCULES HD-6 5W-30



COD. 71883

Specifications: SAE 5W-30; API CK-4; ACEA E6, E7, E9.
Performance level: MB 228.51; Volvo VDS-4.5; Renault RLD-3; MTU TYPE 3.1; DAF.

PRODUCT DESCRIPTION

Oleoblitz **HERCULES HD-6 5W-30** is a low SAPS oil that is suitable for Euro VI and Euro V heavy duty diesel applications including modern, high-output, low emission engines fitted with emission control systems using DPF, SCR, DOC and EGR technologies. It is also suitable for older turbocharged and naturally aspirated diesel engine generations, both on-highway and off-highway, running on high or ultra-low Sulphur diesel and bio-diesel.



HERCULES HD-6 10W-40

COD. 71884

Specifications: SAE 10W-40; API CI-4; ACEA E6, E7.
Performance level: MB 228.51; Volvo VDS-3; Renault RLD-2; MTU TYPE 3.1; MAN M3477, M3271-1.



HERCULES HD-7

COD. 71741

Specifications: SAE 15W-40; API CI-4; ACEA E7.
Performance level: MB 228.3; Volvo VDS-3; Renault RLD-2; MTU TYPE 2; IVECO 18-1804 CLASS T2 E7; MAN M3275.



HERCULES 15W-40

COD. 71740

Specifications: SAE 15W-40; API CF-4.
Performance level: MIL-L-2104 F; MB 228.1; Volvo VDS; MTU TYPE 1; MAN M271.



HERCULES ENERGY

COD. 71746

Specifications: SAE 5W-30; API CF; ACEA E4, E7.
Performance level: MB 228.5; Volvo VDS-3; Renault RLD-2; MTU TYPE 3; DAF; Deutz DQC IV-10; Scania LDF-3; IVECO 18-1804 CLASS TFE; MAN M3277.



HERCULES 140

COD. 71744

Specifications: SAE 10W-40; API CI-4; ACEA E4, E7.
Performance level: MB 228.5; Volvo VDS-3; Renault RLD-2; MTU TYPE 3; IVECO 18-1804 CLASS T3 E4; MAN M3277.



ERA 40

COD. 70388

Specifications: SAE 40; API CE/SF.
Performance level: MIL-L-2104 F (level).



GEAR 75W-80



COD. 77465

Specifications: SAE 75W-80; API GL-4.
Performance level: Ford WSD-M2C200-C; Honda MTF; Renault MTF type NFP; Volvo 97308.

PRODUCT DESCRIPTION

Oleoblitz **GEAR 75W-80** is a Manual Transmission Fluid delivering optimized synchronizer performances and component durability for today's manual gearboxes over their standard service life.



GEAR 90-5

COD. 77466

Specifications: SAE 80W-90; API GL-5;
Performance level: MIL L - 2105 D; ZF TE-ML 16B, 17B, 19B, 21A; IVECO 18-1805 Class RAM 1.



MATIC DEX II

COD. 77467

Performance level: Dexron II D; CAT TO 2; Allison C4; IVECO 18-1807 Class AG2.



GEAR 140-5

COD. 77468

Specifications: SAE 85W-140; API GL-5.
Performance level: MIL L - 2105 D; ZF TE-ML 16D, 21A; IVECO 18-1805 Class RAM 2.



GEAR S90-5

COD. 77469

Specifications: SAE 75W-90; API GL-5.



GEAR 80-4

COD. 77470

Specifications: SAE 75W-80; API GL-4.
Performance level: ZF TE-ML 02L; IVECO 18-1807 Class MGS1.



MATIC DEX III

COD. 77471

Performance level: Dextron III; Allison C4; ZF TE-ML 03D, 05L, 09, 14A, 17C, 21L; Voith H55.6335.xx; IVECO 18-1807 ClassE AG3/III.



GEAR 90-4

COD. 76991

Specifications: SAE 80W-90; API GL-4.



AGRICOIL UTTO



COD. 76753

Specifications:

SAE 10W-30; API GL-4.

Performance level:

ZF TE-ML 03E, 05F, 17E, 21F;
CAT TO-2; Allison C4;
Denison HF-0/HF-2;
Ford M2C 134D;
John Deere JDM J20C;
Massey Ferguson CMS M1145;
Massey Ferguson CMS M1143;
Massey Ferguson CMS M1141;
Massey Ferguson CMS M1135.

PRODUCT DESCRIPTION

Oleoblitz **AGRICOIL UTTO 10W-30** is a Universal Tractor Transmission Oil (U.T.T.O.) dedicated to agricultural and construction machinery. Perfect solution for high and long-lasting performances for your hard-daily work. Oleoblitz **AGRICOIL UTTO 10W-30** is suitable for transmissions, final drives, hydraulic systems and wet brakes of farm tractors and machineries.



AGRICOIL STOU-15

COD. 76754

Specifications: SAE 15W-40; API CF-4/SF;
API GL-4.

Performance level: ZF TE-ML 06B, 07B;
CAT TO 2; Massey Ferguson CMS 1144;
Massey Ferguson CMS 1139; Ford M2C 159-B/C;
JD J27.



HYDRA 46 HV



COD. 77007

Specifications:

DIN 51524 Part III HVLP;
ISO VG 46.

PRODUCT DESCRIPTION

Oleoblitz **HYDRA 46 HV** is a high viscosity index hydraulic fluid for the hydraulic systems of trucks, forklift trucks, earthmoving machinery, combine harvesters and farm machinery. Oleoblitz **HYDRA 46 HV** provides improved operation of the hydraulic system due to its water resistant, antiwear and antirust properties and thermal oxidation stability, with a wider operating temperature compared to monograde hydraulic fluids.



HYDRA 68 HV

COD. 77008

Specifications: DIN 51524 Part III HVLP;
ISO VG 68.



HYDRA 46

COD. 77004

Specifications: DIN 51524 Part II HLP;
ISO VG 46.

Performance level: DENISON HF-2.



HYDRA 68

COD. 77005

Specifications: DIN 51524 Part II HLP;
ISO VG 68.

Performance level: DENISON HF-2.



ART RED



COD. 77002

Specifications:
ASTM D 3306 TYPE 1-FF.

PRODUCT DESCRIPTION

Oleoblitz **ART RED** is a concentrated protective coolant OAT (Organic Acid Technology) for cooling/anti-freezing systems and radiators where organic inhibitors technology is required. Oleoblitz **ART RED** is suitable for cars, vans and trucks, providing an optimized protection even under severe operating conditions.

It helps preventing cavitation and galvanic corrosion. To be mixed with water at a selected percentage depending on targeted freezing point.



ART BLUE

COD. 77000

Specifications: ASTM D 3306 TYPE 1-FF.



ART BLUE READY

COD. 77001

Specifications: ASTM D 3306 TYPE 3;
ASTM D 6210 TYPE 3-FF.



ALT BF-4



COD. 76999

Specifications:
FMVSS No. 116 DOT 4.

PRODUCT DESCRIPTION

Oleoblitz **ALT BF-4** is a brake and clutch fluid for cars, vans and trucks, providing optimized lubricity and protection of the hydraulic and braking system. It provides fading resistance and braking efficiency over the service life.



GROB-2



COD. 77472

Specifications:
NLGI 2.

PRODUCT DESCRIPTION

Oleoblitz **GROB-2** is a grease for general lubrication of articulated joints, universal joints, guides, crank mechanisms mounted on Agricultural Machines and Earth Moving Machines.



THE IDEAL FLUID RANGE FOR ALL YOUR NEEDS.